

AMSOIL Material Safety Data Sheet

Date Issued/Revised: March 17, 2000
Supersedes: January 1, 1997

Section 1: Product and Company Identification

Manufacturer: AMSOIL, Inc. Telephone: 925 Tower Avenue CHEMTREC (Spill Emergency Only): 1-800-424-9300 Superior, WI 54880 Information: 715-392-7101


Product Codes	SGH ISO 32	SGI ISO 46	SGJ ISO 68	SGK ISO 100	
Product Codes	SGL ISO 150	SGM ISO 220	SGN ISO 320	SGO ISO 460	SGP ISO 680

Product Label Name.....Synthetic EP Industrial Gear Oil
Product Use LUBRICATING OIL

Section 2: Composition/Information on Ingredients

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)
1-Decene, Homopolymer, Hydrogenated Base, CAS# Mixture, 85-95%
*See Section 8 for exposure limits.

NFPA & HMIS Rating



Section 3: Hazards Identification

POTENTIAL HEALTH EFFECTS: Minor eye, inhalation and skin irritant.
*See Section 11 for toxicological information.

Section 4: First Aid Measures

EYE: Flush with water for 15-20 minutes. Seek medical attention if irritation develops.

SKIN: Wash immediately with soap and water. Remove contaminated clothing and launder before reuse. Discard shoes and leather articles saturated with the product. Obtain medical advice if irritation occurs.

INHALATION: Remove exposed person to fresh air. If breathing is labored give oxygen. If breathing has stopped apply artificial respiration. Get immediate medical attention.

INGESTION: DO NOT INDUCE VOMITING. If conscious, give 2 glasses of water. If vomiting does occur, keep head below hips to reduce risk of aspiration. Get immediate medical attention.

Section 5: Fire Fighting Measures

FLAMMABILITY PROPERTIES:

	SGH ISO 32	SGI ISO 46	SGJ ISO 68	SGK ISO 100	
Flash Point	493°F(256°C)	493°F(256°C)	500°F(260°C)	475°F(246°C)	
	SGL ISO 150	SGM ISO 220	SGN ISO 320	SGO ISO 460	SGP ISO 680
Flash Point	478°F(248°C)	486°F(252°C)	475°F(246°C)	475°F(246°C)	471°F(244°C)

Method COC ASTM D-92
LFL/UFL.....Not Determined
Auto-ignition TemperatureNot Determined

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, and alcohol foam.

FIREFIGHTING EQUIPMENT: Full bunker gear recommended including a positive pressure self-contained breathing apparatus.

AMSOIL Material Safety Data Sheet

Date Issued/Revised: March 17, 2000
Supersedes: January 1, 1997

Section 6: Accidental Release Measures

Isolate spill area. Provide adequate ventilation. Wear appropriate personal protection. Recover free product for recycle and/or disposal. Add sand, earth or other suitable absorbent to spill area. Prevent entry into sewers and waterways. Check under Transportation and Labeling (DOT/CERCLA) and Other Regulator Information Section (SARA) for hazardous substances to determine regulatory reporting requirements for spill.

Section 7: Handling and Storage

HANDLING: Keep containers closed. Avoid contact with eyes, skin or clothing. Wash hands after handling. Empty container may retain product residue which may exhibit hazards of product.

STORAGE: Keep away from heat or flame.

Section 8: Exposure Controls/Personal Protection

VENTILATION: Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure limits.

RESPIRATORY: Use a NIOSH approved respirator when necessary.

SKIN: Use Viton or Nitrile gloves to avoid prolonged or repeated skin contact.

EYE: Use splash goggles or face shield where splashing is expected or can occur.

EXPOSURE LIMITS: The Threshold Limit Value (TLV) of 5 mg/m³ is suggested for oil mist.

Section 9: Physical and Chemical Properties

	SGH ISO 32	SGI ISO 46	SGJ ISO 68	SGK ISO 100	SGL ISO 150	SGM ISO 220
Physical State	Liquid					
Boiling Point	Not Determined					
Freezing/Melting Point	-76°F(-60°C)	-69°F(-56°C)	-60°F(-51°C)	-60°F(-51°C)	-46°F(-45°C)	-49°F(-45°C)
Vapor Pressure	Negligible					
Vapor Density (Air=1)	Not Determined					
Evaporation Rate	Not Determined					
Solubility in Water	Negligible					
Specific Gravity (Water=1)	0.8443	0.8478	0.8534	0.8591	0.8654	0.8745
Density, lb./gal.	7.031	7.060	7.107	7.155	7.207	7.283
Volatility (Volume)	Not Determined					
VOC	Not Determined					
pH	Essentially Neutral					
Odor	Mild, Bland Hydrocarbon Odor					
Odor Threshold	Not Determined					
Appearance	Light Straw Transparent Fluid					
Viscosity, cSt @ 100°C	6.09	7.52	10.24	13.52	17.82	22.49
Viscosity, cSt @ 40°C	33.50	44.75	68.85	100.79	149.78	220.26
Viscosity Index	130	134	134	132	125	125

	SGN ISO 320	SGO ISO 460	SGP ISO 680
Physical State	Liquid		
Boiling Point	Not Determined		
Freezing/Melting Point	-40°F(-40°C)	-40°F(-40°C)	-33°F(-36°C)
Vapor Pressure	Negligible		
Vapor Density (Air=1)	Not Determined		

AMSOIL Material Safety Data Sheet

Date Issued/Revised: March 17, 2000
Supersedes: January 1, 1997

Evaporation Rate	Not Determined		
Solubility in Water	Negligible		
Specific Gravity (Water=1)	0.8772	0.8811	0.8866
Density, lb./gal.	7.305	7.338	7.384
Volatility (Volume)	Not Determined		
VOC	Not Determined		
pH	Essentially Neutral		
Odor	Mild, Bland Hydrocarbon Odor		
Odor Threshold	Not Determined		
Appearance	Light Straw Transparent Fluid		
Viscosity, cSt @ 100°C	28.8	36.11	48.21
Viscosity, cSt @ 40°C	312.67	433.14	659.85
Viscosity Index	125	125	125

Section 10: Stability and Reactivity

STABILITY: Stable under moderately elevated temperatures and pressures.

INCOMPATIBILITY: Avoid contact with strong oxidants.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION OF PRODUCT: Toxic oxides of carbon, aldehydes and other products of incomplete combustion.

Section 11: Toxicological Information

ACUTE EXPOSURE

- Eye Irritation: Moderate to strong eye irritation. Based on data from components or similar material.
- Skin Irritation: Not expected to be a primary skin irritant. Based on data from components or similar material. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, defatting, and cracking of the skin.
- Respiratory Irritation: If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract similar to that observed with mineral oil. Based on data from components or similar materials. Under good industrial hygiene practices where all exposure limits are observed, respiratory irritation should not be a problem.

CHRONIC EXPOSURE

- Chronic Toxicity: No data available to indicate product present at greater than 1.0% are chronic health hazards.
- Carcinogenicity: No data available to indicate product present at greater than 0.1% are a carcinogenic hazard.
- Mutagenicity: No data available to indicate product present at greater than 1.0% present a mutagenic or genotoxic hazard.
- Reproductive Toxicity: No data available to indicate product present at greater than 1.0% present a reproductive hazard.
- Teratogenicity: No data available to indicate product present at greater than 1.0% present a teratogenic hazards.

ADDITIONAL INFORMATION

Exposure Limits: Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter.

Section 12: Ecological Information

No data available on the adverse effects of this product on the environment.

Section 13: Disposal Considerations

If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Section 14: Transport Information

This product is not classified as hazardous material for DOT shipping. For further information relative to spills resulting from transportation incidents, refer to the latest DOT Emergency Response Guidebook for Hazardous Materials.

Section 15: Regulatory Information

U.S. Federal Regulations

- OSHA Table Z..... Synthetic Base Stock (mist)
- TSCA Not Applicable
- CERCLA 40 CFR 302.4 Not Applicable
- SARA Title III
 - Section 302 Extremely Hazardous Not Applicable
 - Section 311/312
 - Fire Hazard Yes
 - Reactive Hazard No
 - Release of Pressure No
 - Acute Health Hazard Yes
 - Chronic Health Hazard No
 - Section 313 Toxic Chemical Not Applicable

U.S. State Regulations

- California (Prop 65)
 - Does not contain chemicals known to the state of California to cause cancer.

International Regulations

- WHMIS All components listed

Section 16: Other Information

The information and recommendations contained herein are, to the best of AMSOIL's knowledge and belief, accurate and reliable as of the date issued. AMSOIL makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and AMSOIL shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with AMSOIL's interpretation of the available data.